



DAHUA THERMAL TEMPERATURE MEASUREMENT SYSTEM

OPTIONS



OPTION 1 - STAND-ALONE THERMAL CAMERA

PRODUCT	PART NUMBER	QUANTITY
Thermal Camera	TPC-BF2221-HTM	1
Blackbody	TPC-HBB-CHW	1
Tripod	VCT-999	2
Mounting Plate	RQW026-00	2
Kettle Lead	UKPLUG	1
PoE Switch	PFS3010-8ET-96	1



- View LIVE temperature readings on web browser.
- Receive BTM alerts via camera built in white light strobe & siren, relay output.
- Record to SD card.

REQUIRES A STAND ALONE PC/LAPTOP AND MONITOR FOR PROGRAMMING & VIEWING

OPTION 2 - THERMAL CAMERA & BASIC NVR

PRODUCT	PART NUMBER	QUANTITY
Thermal Camera	TPC-BF2221-HTM	1
Blackbody	TPC-HBB-CHW	1
Tripod	VCT-999	2
Mounting Plate	RQW026-00	2
Kettle Lead	UKPLUG	1
NVR	NVR2104HS-P-1TB	1
22" Monitor	JGM-215VH	1



- View LIVE temperature readings on NVR monitor or web browser
- Receive BTM alerts via camera built in white light strobe & siren, relay output
- Record to NVR (Continuous only, no event logging)
- Power camera from NVR

REQUIRES A STAND ALONE PC/LAPTOP FOR PROGRAMMING & VIEWING

OPTION 3 - THERMAL CAMERA & AI NVR

PRODUCT	PART NUMBER	QUANTITY
Thermal Camera	TPC-BF2221-HTM	1
Blackbody	TPC-HBB-CHW	1
Tripod	VCT-999	2
Mounting Plate	RQW026-00	2
Kettle Lead	UKPLUG	1
NVR	NVR5216-16P-I-1TB	1
22" Monitor	JGM-215VH	1
PoE Switch	PFS3010-8ET-96	1



- View LIVE temperature readings on NVR monitor or web browser
- Receive BTM alerts via camera built in white light strobe & siren, relay output
- Receive BTM alerts on NVR monitor and other NVR output features (Email, Buzzer etc)
- Search and review historical BTM events on the NVR
- Up to 4 channels of backend face mask detection OR facial recognition
- This option still requires PoE switch

REQUIRES A STAND ALONE PC/LAPTOP AND MONITOR FOR PROGRAMMING & VIEWING

OPTION 4 - THERMAL CAMERA & DSS EXPRESS

PRODUCT	PART NUMBER	QUANTITY
Thermal Camera	TPC-BF2221-HTM	1
Blackbody	TPC-HBB-CHW	1
Tripod	VCT-999	2
Mounting Plate	RQW026-00	2
Kettle Lead	UKPLUG	1
PoE Switch	PFS3010-8ET-96	1
DSS Base License		1
15 NUC PC	SC-COMPUTER	1
22" Monitor	JGM-215VH	1
Keyboard & Mouse	SC-KEYBOARD	1



- View LIVE temperature readings on web browser or DSS Express
- Receive BTM alerts via camera built in white light strobe & siren, relay output and DSS Express software
- Record BTM events to DSS/PC + Search and review historical BTM events

OPTION 5 - THERMAL CAMERA & BASIC NVR & DSS EXPRESS

PRODUCT	PART NUMBER	QUANTITY
Thermal Camera	TPC-BF2221-HTM	1
Blackbody	TPC-HBB-CHW	1
Tripod	VCT-999	2
Mounting Plate	RQW026-00	2
Kettle Lead	UKPLUG	1
DSS Base License		1
NVR	NVR2104HS-P-1TB	1
PoE Switch	PFS3010-8ET-96	1
I5 NUC PC	SC-COMPUTER	1
22" Monitor	JGM-215VH	1
Keyboard & Mouse	SC-KEYBOARD	1



- View LIVE temperature readings on web browser, NVR monitor or DSS Express
- Receive BTM alerts via camera built in white light strobe & siren, relay output and DSS Express software
- Record BTM events to DSS/PC + Search and review historical BTM events
- Record to NVR (Continuous only, no event logging)
- Power camera from NVR

OPTION 6 - THERMAL CAMERA & AI NVR & DSS EXPRESS

PRODUCT	PART NUMBER	QUANTITY
Thermal Camera	TPC-BF2221-HTM	1
Blackbody	TPC-HBB-CHW	1
Tripod	VCT-999	2
Mounting Plate	RQW026-00	2
Kettle Lead	UKPLUG	1
PoE Switch	PFS3010-8ET-96	1
DSS Base License		1
NVR	NVR5216-16P-I-1TB	1
I5 NUC PC	SC-COMPUTER	1
22" Monitor	JGM-215VH	1
Keyboard & Mouse	SC-KEYBOARD	1



- View LIVE temperature readings on web browser, NVR monitor or DSS Express
- Receive BTM alerts via camera built in white light strobe & siren, relay output and DSS Express software
- Record BTM events to DSS/PC + Search and review historical BTM events
- Receive BTM alerts via camera built in white light strobe & siren, relay output
- Receive BTM alerts on NVR monitor and other NVR output features (Email, Buzzer etc)
- Search and review historical BTM events on the NVR
- Up to 4 channels of backend face mask detection OR facial recognition
- This option still requires PoE switch

